



Scoreboard Specifications

Overall size: 8' (W) x 6' (H) x 4" (D)

Approximate Weight: 210 lbs

Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.

Incoming Mains Power and Data Location: TOP of the Scoreboard

MAX Current Draw: 5.6 Amps

14" LED Digits for TIME

10" LED Digits for HOME, GUEST, PERIOD

7" LED Digits for TM FOULS, TOL, PLAYER FOULS

2" LED Dots

5" Electronic Team Names at 8 CHARACTERS

4" White Vinyl Lettering for PERIOD, TM FOULS, TOL, PLAYER FOULS

3" White Vinyl Lettering for P. TO. B

Optional AD space:

LEFT: 24.5" (W) X 24" (H)

RIGHT: 19.5" (W) X 24" (H)

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	7/13/2021

<p>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</p> <p>OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.</p>		<p>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</p>	
TOLERANCE INFORMATION Dimensions are in Inches	THIRD ANGLE PROJECTIONS	SIZE	REV
Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'		A	A
<p>SCALE NTS</p>		<p>FILENAME M5008BICE</p> <p>INIT DRAWING DATE 7/13/21</p> <p>USAGE USE FOR REVIEW</p>	<p>DRAWN BY CGTHOMPSON</p> <p>PAGE 1 OF 1</p>