



**Scoreboard Specifications**

Overall size: 8' (W) x 6' (H) x 4" (D)  
 Approximate Weight: 197 lbs  
 Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 5 Amps. Requires an earth ground connection.  
 Incoming Mains Power and Data Location: TOP of the Scoreboard  
 MAX Current Draw: 2.9 Amps

14" LED Digits for TIME  
 10" LED Digits for HOME, GUEST, PERIOD  
 7" LED Digits for TM FOULS, TOL, PLAYER FOULS  
 2" LED Dots

8" White Vinyl Lettering for HOME, GUEST  
 4" White Vinyl Lettering for PERIOD, TM FOULS, TOL, PLAYER FOULS  
 3" White Vinyl Lettering for P. TO. B

Optional AD space:  
 LEFT: 24.5" (W) X 25" (H)  
 RIGHT: 19.5" (W) X 25" (H)

- All LED digits include the following:
- \* Shatter Resistant Lexan cover
  - \* Conformal coating to protect from environmental conditions
  - \* Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	7/13/2021

<p>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</p> <p>OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.</p>		<p>4056 Blakie Road,          London, ON, N6L 1P7          Tel: (519) 652-5833          Fax: (519) 652-3795          Email: oes@oes-inc.com</p>	
SIZE	FILENAME	INIT DRAWING DATE	REV
A	M5008BICV	7/13/21	A
USAGE		USE FOR REVIEW	
SCALE	NTS	DRAWN BY	CGTHOMPSON
		PAGE	1 OF 1

TOLERANCE INFORMATION  
 Dimensions are in Inches

Fractional ± 1/16"  
 Two Place Decimals ± 0.02"  
 Three Place Decimals ± 0.005"  
 Four Place Decimals ± 0.0005"  
 Angular ± 30'

