



Render sponsor messages and game statistics with stunning clarity at your next indoor event. OES's scoring tables give you the perfect venue for increasing fan engagement - while increasing revenue.

Manage your media and customize what gets displayed with OES' Bolt software. Bolt gives you command of your video display content with flexible positioning and easy-to-program animations for maximum impact.



Easily broadcast and entertain spectators with a steady stream of live video feeds, sponsor ads, team messages, still and motion graphics with Bolt, OES' live event production suite. For an enhance viewing experience, connect Bolt to your OES controller and display a wide range of real time scoring and stats information during your event.



	P4	P6	P10
Pitch (mm)	4	6	10
Brightness (nits)	1200	1800	1600
Resolution (WxH)	160x160	160x120	96x72
Size (WxHxD)	640 x 640 x 140mm	960 x 720 x 140mm	960 x 720 x 140 mm
Weight	12Kg (Aluminum Cabinet)	20Kg (Aluminum Cabinet)	20Kg (Aluminum Cabinet)
Viewing Angle (h/v)	160/160	160/160	160/160
Scan Rate	1/16	1/8	1/4
Grey Scale (Levels/Color)	4096-16384	4096-16384	4096-16384
Display Refresh Rate (Hz)	1920	1920	1920
Video Frame Rate (HZ)	60	60	60
Contrast Ratio	3000:1	3000:1	3000:1
Colors	68.7 Billion 4.4 Trillion	68.7 Billion - 4.4 Trillion	68.7 Billion - 4.4 Trillion
Processing Depth (bit)	12-14 bit	12-14 bit	12-14 bit
Input Voltage (Vac)	100-24	100-24	100-24
Input Power Max (W/m2)	0 600	0 400	0 400
Input Power Avg (W/m2)	210	140	140
Input Frequency (Hz)	50-60	50-60	50-60
Lifetime (Hours)	100,000	100,000	100,000
Service Access	Front & Rear	Front & Rear	Front & Rear
Agency Approvals	ETL & FCC	ETL & FCC	ETL & FCC