

Scoreboard Specifications

Overall size: 6' (W) x 4' (H) x 6" (D)

Approximate Weight: 172 lbs

Incoming Mains Power: (1x) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.

Incoming Mains Power and Data Location: Behind the [TIME] Digit(s).

14" LED Digits for TIME



10" LED Digits for SCORE, PERIOD

6" White Vinyl Lettering for ALL

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	12/20/2021

<p>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</p> <p>OES INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.</p>		 <p>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</p>	
TOLERANCE INFORMATION Dimensions are in inches	THIRD ANGLE PROJECTIONS	SIZE	INIT DRAWING DATE
Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'		B	12/20/21
		FILENAME	REVISION
		M3006AUXV	A
		USAGE	
		USE FOR REVIEW	
SCALE	DRAWN BY	PAGE	
NTS	RDONALD	1 OF 1	