CFM4100/CFM4200

GEM 400

For bench presses and automatic machines



Powerful, Proven, Crimp Defect Detection A robust, reliable performer for detecting wire crimping defects and providing 100% traceability

Supports up to 2 channels!

Proven Wire Crimp Analysis 100% Traceability

- The system captures the crimp force signature over time, and compares this signature to the reference or "learned" signature using OES's patented CDA algorithm
- 3-zone analysis is performed for world-class discrimination between normal and abnormal cycle signatures that identify a defective crimp

Operator Friendly Interface

- Graphic LCD backlight for visual indication of crimp failure
- Common icons and onetouch processes make it easy to get the results you need

FORCEView

- The *ForceView for Windows* software stores all production data for playback or export
- Crimp process data can be logged

Quick Start Setup

- The menu-driven, keypad interface makes setup simple and fast
- Immediately color graphs of crimp process signatures are displayed on *ForceView for Window*s showing any trend relative to configurable upper and lower tolerances.
- Automatic tolerance optimization

Crimp Force Monitoring



Monitoring your wire crimping process and knowing when manufacturing conditions are changing is critical in detecting errors, and eliminating unnecessary scrap.



Direct Machine Control

- Interfaces with press control to stop the crimping when the process signature moves outside of the tolerance limits
- Interface with chopper equipment

Simple to Install

- The universal, flexible bracket can quickly mount the monitor in the most appropriate location
- Includes all the required sensors, cables, connectors and instructions

Simple Connectivity

Connect with your plant-wide network via Ethernet

Model	# of Channels
CFM4100	1
CFM4200	2

Machine Applications		
Bench Press - OEM		
Bench Press - Retrofit		
Automatic Press - OEM		
Automatic Press - Retrofit		
Sensor Options		
OES Piezo Sensor (Strain, Force)		
SenFit TM Base Plate		
SenFit TM Ram Adapter		

Technical Specs

Supply Voltage	100-240 VAC (50-60 Hz)
Communications	1 Ethernet RJ45
	1 USB 2.0 (expandable)
Sensor Inputs	1 and 2
Digital Inputs	2 per channel
Digital Outputs	4 per channel
Display	LCD backlit screen, keypad,
	ForceView TM for Windows
Dimensions	114 x 190 x 65 mm 4.5 x 7.5 x 2.56 inch
	4.5 X 7.5 X 2.56 INCN

Package typically includes:

- CFM4100 or CFM4200 Unit
- ForceView for Windows Software
- Sensor and connecting cables
- Universal, flexible mounting bracket
- Electrical interface cables



About OES Technologies

OES Technologies products and technologies are developed specifically for the wire processing industry to monitor and inspect 100% of parts produced during the manufacturing process, and prevent part defects from entering the supply chain. OES's dedication to innovation enables them to deliver a steady stream of cutting-edge technologies that meet the exacting demands of this ever-changing market.

FORCEWorx®

ForceView for Windows enables operators to set-up and operate the defect detection system. ForceView contains a powerful set of graphical signature analysis tools so you can track production trends and process variations based on preset tolerances. It also captures the crimp process signature of every crimp for 100% traceability.



